



RENOVATION
PERFECTION

Bathroom



Bathroom furniture

Raw, varnishes or painted woods, melamine, laminate;
PVC, stainless steel and metal

Bathroom walls including inside of tiled shower

Ceramic, listels, glass bricks...

PROPERTIES

Renovation Perfection paint has been specially designed to durably renew highly stressed surfaces and materials. Thanks to the combination of specific polymers and the Additiv System, a real booster of performance, it offers a high quality finish, ready to face all the hazards of everydaylife.

THE PAINT TO RENOVATE YOUR BATHROOM



Size: Tester 75ml - 750ml



- Direct on wall tiles and furniture
- High resistance to household products

COLOURCHART

SATIN

WHITE	COTTON VEIL	TAUPE	DEEP BLUE
POWDER PINK	SOFT GREY	DOLPHIN GREY	ANTHRACITE



RENOVATION
PERFECTION

INFOS:

750ml = +/- 10sqm
= 5sqm with 2 coats

Bathroom

8h

Recoat

Water

Tool cleaning

48h

Before 1st shower

TOOLS:



Wide stick
or Paint stirrer



Round edged paint
brush for angles,
corners & finishes



4-5mm short pile roller

PREPARATION

PREPARATION of the surface is ESSENTIAL.

WASHING the surface with a soda-based or sugar soap (alkaline) cleaner is CRUCIAL, insisting on groutings. Remove any silicone sealant before painting. Reseal after application of the paint.

- On non-painted surfaces (wall tiles, glass, laminates.): wash, rinse thoroughly with water then leave to dry.
- On raw / porous surfaces (wood, mdf): lightly sand and remove dust.
- On already painted or varnished surfaces: wash, rinse thoroughly with water, leave to dry, then lightly sand with 240 grit sandpaper and remove dust.

APPLICATION

Apply the paint at room temperature between 12 and 25°C and avoid draughts.

1. Empty the Additiv System (the sachet that is placed under the lid of the tin) into the paint.

Stir the paint for 5 minutes, working around the bottom of the tin with a wide stick to mix it well.

2. Work on small surfaces. Apply from one end to the other. Follow with successive cross strokes. Do not start 2nd coat while it's still drying. Leave to dry for 8h and apply a 2nd coat in the same way.

On horizontal surfaces, the paint has to be covered with the Renovation Perfection worktop varnish.

Once the sachet has been added, the mixture must be used within less than 10 days to maintain optimal adhesion and performance.

V33 TIPS

- To clean your painted surfaces, use a gentle detergent and a non-abrasive sponge.
- Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the rest 20 days after application.

HEALTH AND SAFETY : Contains biocidal products (preservatives) : contains C(M)IT/MIT (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze.

EU limit value for this product (cat A/j - Two-pack reactive performance coatings for specific end use such as floors): 140g/L (2010). This product contains max 4g/L VOC.