

CROWN TRADE FASTFLOW QUICK DRY GLOSS

A water-based, durable gloss finish for use on suitably prepared interior and exterior joinery and metalwork. Fastflow Quick Dry Gloss has excellent opacity, and a high gloss finish, with the added benefit of staying whiter for longer, compared to traditional solvent-borne gloss.

Drying	Touch Dry from 1-2 hours. Recoatable after 4-6 hours. Ensure previous coat is fully dry before application.
Spreading/Coverage	Up to 15m ² / litre depending on surface texture
VOC Content	EU Limit for this product (cat A/d) 130g/l (2010) This product contains max 8g/l
Preparation	All surfaces must be clean, sound and dry before painting. Remove all loose and defective paint coatings. Surfaces contaminated with organic growths should be treated with a suitable Fungicidal solution used in accordance with the manufacturer's recommendations. Remove any rust from metalwork by chipping, scraping and/or abrasion. Make good any surface defects using suitable filler. Rub down surface using a suitable abrasive material to provide a 'key' and produce a smooth, sound surface. Remove all surface contamination, including dust deposits by washing and rinsing with clean water. Treat any knots in wood with an appropriate knotting solution used in accordance with the manufacturer's recommendations. Prime all bare surfaces using an appropriate wood or metal primer, allow to fully dry before applying the finishing coats.
Application	Stir well before use. Apply using a good quality synthetic brush or a good quality micro fibre medium pile roller, to achieve an even thickness. Avoid excessive de-nibbing in-between coats. To assist application on porous substrates the surface may be dampened slightly.
Cleaning	Return surplus material to a container. Wash with clean water immediately after use
Health & Safety	Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains 1,2-benzisothiazol-3(2H)-one and 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.



P O BOX 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG, United Kingdom

Tel: +44 (0)1254 704951

Email: export.crm@crownpaints.co.uk

Website: <http://www.crownpaint.co.uk>