

CROWN RETAIL UNDERCOAT

A high performance, solvent borne proprietary product for interior and exterior use over new and previously painted wood and metal to provide a smooth consistent surface before applying satin or gloss finish products.

Drying	Touch dry 4 - 6 hours. Recoat after 16 hours
Spreading/Coverage	Up to 16m ² per litre on smooth surfaces
VOC Content	EU Limit for this product (cat A/d) 300g/l (2010) This product contains max 299g/l
Preparation	All surfaces must be clean, sound and dry before painting. Remove all loose and defective paint coatings. Surfaces contaminated with organic growths should be treated with a suitable Fungicidal solution used in accordance with the manufacturer's recommendations. Remove any rust from metalwork by chipping, scraping and/or abrasion. Make good any surface defects using suitable filler. Rub down surface using a suitable abrasive material to provide a 'key' and produce a smooth, sound surface. Remove all surface contamination, including dust deposits by washing and rinsing with clean water. Treat any knots in wood with an appropriate knotting solution used in accordance with the manufacturer's recommendations. Prime all bare surfaces using an appropriate wood or metal primer, allow to fully dry before applying the finishing coats.
Application	Stir well before use. Apply by brush to an even thickness (a fine, soft long filament bristle brush gives best results). Maintain a wet edge. On timber lay off in the direction of the grain.
Cleaning	Return surplus material to a container. Wash with a proprietary cleaner immediately after use
Health & Safety	Warning Flammable liquid and vapour. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In case of fire: Use alcohol-resistant foam to extinguish. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains 2-butanone oxime. May produce an allergic reaction.



P O BOX 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG, United Kingdom

Tel: +44 (0)1254 704951

Email: export.crm@crownpaints.co.uk

Website: <http://www.crownpaint.co.uk>