

CROWN WEATHERCOAT SMOOTH MASONARY

A durable, water based matt exterior wall finish containing a tough, flexible resin and quality light fast pigments to provide a weather resistant, smooth coating. Suitable for the protection and decoration of exterior cement, stone, pre-cast concrete, render and roughcast.

Drying	Under normal drying conditions, surface dry after 2 hours and recoatable after 4-6. Allow for adequate ventilation during the drying period
Spreading/Coverage	Up to 12.8m ² / litre depending on surface texture and porosity
VOC Content	EU Limit for this product (cat A/c) 40g/l (2010) This product contains max 1 g/l VOC
Preparation	All surfaces must be clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose and failing material by scraping or brushing with a stiff bristle brush (not wire) to a sound edge. Surfaces contaminated with organic growths should be treated with a suitable Fungicidal solution used in accordance with the manufacturer's recommendations. Make good any surface defects using suitable filler used in accordance with the manufacturer's recommendations. Remove all surface contamination by washing thoroughly and rinsing with clean water. Prime all bare, porous, powdery or repaired areas using suitable Stabilising Solution, allow to fully dry before applying the finishing coats.
Application	Stir well before use. Apply by brush, medium or long pile roller depending on surface texture, or by airless spray. For airless spray use a minimum fluid pressure of 2000psi (136 bar) and a minimum tip size of 0.018 thou. Mask as necessary with a wet strength grade masking paper.
Cleaning	Return surplus material to a container. Wash with clean water immediately after use
Health & Safety	Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (mixture 3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.



P O BOX 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG, United Kingdom

Tel: +44 (0)1254 704951

Email: export.crm@crownpaints.co.uk

Website: <http://www.crownpaint.co.uk>