




POLYURETHANE SEALANT

A one component elastomeric based polyurethane sealant. It forms a highly elastic, tear and weather resistant joint. **DYNA-PRO® Polyurethane Sealant** offers good adhesion without primer on usual materials such as glass, stone, ceramic tiles, polyester, anodized aluminum, concrete, wood, most lacquered metals etc.

Approvals



Features

- Easy to apply
- Good adhesion
- PHTHALATE free
- Good UV and weather resistance properties
- Excellent quality and stability
- No sagging
- Good extrusion rate



Technical Data

Property	Unit	Value
Skin over time (23°C / 50% RH)	Min	70
Density @ 20°C	g/ml	1.16 (Black) 1.18(Others)
Temperature Resistance	°C	-40 to +100
Application Temperature	°C	+5 to +35
Shore A Hardness		40
Overall Appearance		Pasty
Elongation at break	%	>500
Coloring Resistance		Very Good
Water Resistance		Not suitable for continuous water immersion

Surface Preparation

Surfaces must be clean, dry and free from grease, dust, oil and any contaminant possibly harming the bonding. It is recommended to clean the surface with a suitable solvent such as methylethylketone, acetone etc.

Shelf Life

15 months from date of production, when stored at or below 30°C in the original unopened container

Instructions

Apply using a manual or a pneumatic gun. Once applied, smoothen the joint with a putty knife dipped in soapy water. Once the cartridge is opened, the product should be used within 24 hours; Otherwise, it could harden. Do not apply at temperatures below 5°C. During curing, avoid contact with non-cured polyurethanes, silicone sealants and alcohols.

Packaging

- 300 mL cartridge
- 600 mL sausage

Standard Colors

