


## ACRYLIC FOR WOOD



Superior interior/external mono-component acrylic for wood sealant for general construction, especially with wood and wood colored material. Sealant is paintable, flexible and easy to apply. It exhibits excellent adhesion to building substrates and is slump resistant. Short skinning and drying time. Performance up to 15 years.

### Approvals



## Features

- Movement of up to 15%
- Indoor & Outdoor Use
- Paintable 3 hours after application
- Low odor
- Aging Resistance
- Solvent Free (water-based)



## Surface Preparation

Surfaces must be clean, dry and free of grease, dust and frost. In case of renovation work, old sealant as well as old paint must be removed completely. It is recommended to apply a suitable back-up material (closed cell polyethylene backer rod or PE-foil) on the bottom of the joint to prevent the sticking of the sealant to the back of the joint.

## Instructions

Sealant joint width should be designed to accommodate movement capability of sealant. Avoid application of the sealant during extreme temperature variations. Strict adherence to joint design process required (**operational ability of DYNA-PRO® Acrylic can only be granted in case of correct processing as follows**). Minimum joint width: 6mm. For joints 6-12mm wide, seal depth is 6mm. Above this range, apply width to depth ratio rule of 2:1 (12mm being the maximum). For joint dimensions greater than 25mm, please contact DYNA-PRO® Technical Service department. In situations where fillet joints are needed, a minimum of 6mm sealant bite to each substrate is recommended. Sealant may be tooled with water or a neutral non-dyeing tooling liquid.

## Technical Data

| Property                     | Unit              | Value       |
|------------------------------|-------------------|-------------|
| Hardness (Shore A)           |                   | 30          |
| Application Temperature      | ° C               | +5 to +50   |
| Temperature Resistance       | ° C               | -25 to +80  |
| Skin-over time               | Min               | 15-30       |
| Specific Gravity             | g/cm <sup>3</sup> | (1.60±0.05) |
| Full Cure @ room temperature | cm                | 1-4         |

## Priming

Porous substrates, e.g. concrete and untreated wood should be pre-treated with a diluted sealant (DYNA-PRO® Acrylic with water in a ratio of 1:1 to 1:5). Before applying primer remove cement grouts, release agents and oil coatings.

DYNA-PRO® Acrylic should not be used in sanitary areas, on marble / natural stone, on bituminous substrates and untreated (not primed) metallic substrates

## Shelf Life

18 months from date of production, when stored at or below 30°C in the original unopened container

## Packaging

- 280 / 300 mL cartridge

## Standard Colors

