



DESTINATION

Protection for horizontal surfaces (worktop, vanity top) painted with Renovation Perfection paint.

PROPERTIES

The Renovation Perfection protection has been specially designed to durably protect highly stressed surfaces and materials. Thanks to the combination of specific polymers and of the Additiv System, a true performance booster, it protects the Renovation Perfection paint from impacts and scratches specific to worktops.

A VARNISH TO PROTECT YOUR PAINTED WORKTOPS



Size : 500ml



- **Anti-scratch protection for worktops**
- **Ultra resistance to stains, grease**

COLOURCHART

Clear
Satin

INFOS:**500ml = +/- 5sqm
= 2,5sqm with 2 COATS****4h**

Recoat

Water

Tool cleaning

24h

Fully dry

TOOLS:**Round edged paint brush**
(for angles, corners & finishes)**Laquer roller****PREPARATION**

The Renovation Perfection Protection is essential to reinforce the resistance of horizontal surfaces repainted with the Renovation Perfection Paint. Wait for complete drying of the paint before application of the protection.

APPLICATION

1. Empty the Additiv System (the sachet that is placed under the lid of the tin) into the protection. Stir for 5 minutes to mix it well.
2. Apply the protection in 2 layers evenly, in crossed layers to ensure the performance of the protection and a neat finish.

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

V33 TIPS

- The protected surface can be easily maintained with your usual household products.

HEALTH AND SAFETY : Contains biocidal products (preservatives): contains C(M)IT/MIT (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j - Two-pack reactive performance coatings for specific end use such as floors): 140g/L (2010). This product contains max 49g/L VOC.